



RFID Reader STA SL500

Being developed based on NXP RFID technology, SL500 series desktop reader/writer are classified into SL500L, SL500A, SL500D and SL500F four types, the below sheet shows its category and price message. These proximity readers support ISO14443A, ISO14443B and ISO15693 passive cards, tags and labels. Free SDK is provided, it helps an engineer to programming his/her own applications. The package is composed of PC_DEMO software, WinAPI and prototype description, USB driver, sample source code in C#, VC, BC, VB, PB and DELPHI.



Model		RFID Reader SL500						
Frequency		13.56MHz						
Tag supported		ISO14443A, ISO14443B, ISO15693						
Interface		RS232/USB						
Temperature range		-20° - +50°						
Dimension		110 × 80 × 26 mm						
Weight		100g						
System		Windows 98 \ 2000 \ XP \ NT \ ME \ Vista						
	SL500L -RS232	SL500L -USB	SL500A -RS232	SL500A -USB	SL500D -RS232	SL500D -USB	SL500F -RS232	SL500F -USB
Protocol	ISO14443A		ISO14443A		ISO15693		ISO14443A ISO14443B ISO15693	
Tags supported	FM11RF08, Ultralight, NTAG203, Ultralight C, MIFARE Mini, MIFARE™ Classic 1K, MIFARE™ Classic 4K		FM11RF08, Ultralight, NTAG203, Ultralight C, MIFARE Mini, MIFARE™ Classic 1K, MIFARE™ Classic 4K, DESFire, MIFARE ProX		I.CODE SLI, Tag_it HFI		FM11RF08, Ultralight, NTAG203, Ultralight C, MIFARE Mini, MIFARE™ Classic 1K MIFARE™ Classic 4K, DESFire, MIFARE ProX, AT88RF020, SR176, SR1X4K, I.CODE SLI, Tag_it HFI, T = CL Smart card ,	

STALLION SYSTEMS AND SOLUTIONS PVT. LTD.

Stallion House, Paadam Stop, K.P.Vallon Road, Kadavanthra, Kochi-682 020.

Phone : +91 484 2314592, 2312986, 2310224, 2320161, 2320162 Fax: +91 484 2313108.

E-mail : sales@stallionindia.com