

0045565553





CRUISE 2

The New Generation of CRUISE Series



:65555

~ N5565555

A new generation of CRUISE equipment has been introduced by Seuic, based on its star product "CRUISE1P" - CRUSIE2, which has many advantages in terms of performance, reliability, and operation experience compared to the first-generation CRUISE, with good grip and easy operation. In addition, many improvements have been made to offer the front-line employees a better operating experience and increase their efficiency.

, 45565553



045565553

Product Features



Strong core and performance


Qualcomm Snapdragon octa-core 2.0 GHz processor, running performance is 100% higher than the first generation of CRUISE so that a variety of applications can be used smoothly





high-speed Wi-Fi transmission

The latest Wi-Fi 6 ready technology, compared to the first generation, has significantly improved connection stability and transmission distance. In addition, despite dense three-dimensional shelving in large warehouses, it is smooth to connect for real-time data transmission











045565553

Specifications Physical Ct.

| | Physical Characteristics | | |
|----------|--------------------------|--|--|
| | Dimensions | Standard battery model: | |
| | | 6.1 in. L x 3 in. W x 0.5 in. H | |
| | | 156 mm L x 76 mm W x 13.9 mm H | |
| | | 6000mAh battery model: | |
| | | 6.1 in. L x 3 in. W x 0.6 in. H | |
| | | 156 mm L x 76 mm W x 16.4 mm H | |
| | Weight | 9.0 oz./255 g (5000mAh model) | |
| | | 9.8 oz./279 g (6000mAh model) | |
| - 6 | Display | 5.5 in. color HD (720 x 1440) | |
| 39455655 | Touch Panel | Capacitive touch, supporting wet hand mode and glove | |
| 2011 | | mode | |
| | Power | Detachable 5000mAh Li-ion rechargeable battery with | |
| | | hot-swap, optional 6000mAh | |
| | | 40mAh Li-ion spare battery | |
| | Expansion Slot | Maximum compatible storage: 128GB | |
| | Interface/ | Waterproof Type-C USB interface, supporting Type-C | |
| | Communicatio | earphone, USB2.0 Highspeed, OTG and fast charge | |
| | n | Nano/TF card, card slot with two out of three | |
| | Notifications | Sound, vibrator, LED light indication | |
| | Fingerprint | Support | |
| | (identification | Sapport (Sapport | |
| 3945565 | Keypad | Volume +/ - button, Power ON/OFF button, Left Scan | |
| 1012 | ,,,,,,,, | button, Right Scan button, Custom button, Virtual On- | |
| | | Screen button (Return button, Home button, Menu | |
| | | button) | |
| | Voice and | Speaker, dual microphones, PTT voice (Internal speaker | |
| | Audio | and Bluetooth wireless headset support) | |
| | Performance Cha | racteristics | |
| | СРИ | Qualcomm Octa-core 2.0GHz | |
| | Operating | Android 11, GMS with AER Certified | |
| | System | | |
| | Memory | 4GB RAM/64 GB Flash memory. | |
| | c3 | 6GB RAM/64 GB Flash memory (Optional) | |
| - 5655 | User Environmen | 56555 | |
| 10 V/2.2 | Operating | -4 °F to 131 °F/-20 °C to +55 °C | |
| | Temp. | 3 | |
| | Storage Temp. | Battery included: -40 °F to 158 °F/-40 °C to +70 °C | |
| | Humidity | 5% to 95%, non-condensing | |
| | Drop Spec. | 4.9 ft./1.5 m drops to concrete at room temperature | |
| | Tumble Spec. | 1000 1.6 ft./ 0.5 m tumbles | |
| | Sealing | IP68 | |
| | Electrostatic | ±15 kV air discharge, ±8 kV direct discharge | |
| | Discharge (ESD) | | |
| | Sensor | G-sensor, light sensor, proximity sensor, electronic | |
| ł | 2011001 | S sensor, light sensor, proximity sensor, electronic | |

compass, gyroscope



| | Data Capture | |
|----|--------------------|--|
| | Scanning | Seuic 2D Barcode scanner |
| | | Honeywell SR 2D Barcode scanner |
| | | Camera scanning |
| • | Camera | Front: 5 MP |
| | | Rear: 13 MP autofocus, flash LED with flashlight mode |
| • | NFC | Supports tags ISO15693, ISO14443A/B (without |
| | 0 | encryption protocol), ISO14443A with encryption |
| | | protocol (Mifare One S50,S70 and compatible cards); |
| | -63 | supports NFC Protocol |
| | Wireless Connect | 15/100 |
| 00 | Wireless Connect | 19A55 |
| - | WLAN | 1555 000 11 /1 / / / / / / / / / / / / / / / |
| | WLAN Radio | IEEE 802.11 a/b/g/n/ac/ax ready(2.4G/5G dual-band |
| | | WIFI) protocol |
| | Working | CH1~CH13, CH36-CH140, CH149~CH165 |
| | Channel | |
| | Security of | Supports WPA2 –Personal, WPA2 –Enterprise, WPA3, |
| | WLAN | EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP- |
| | | MSCHAPv2, PEAPv1/EAP-GTC, EAP-SIM, EAP-AKA, |
| | | EAP-AKA Prime |
| | WWAN | |
| | WWAN Radio | GSM:Qual Band(850/900/1800/1900Mhz) |
| | WWAN RADIO | TD-SCDMA:Band34,Band39 |
| 00 | X | WCDMA:Band1,Band2,Band5,Band8 |
| | | CDMA 1x /EVDO:BC0 |
| | | TDD-LTE:Band34,Band38,Band39,Band40,Band41 |
| | | FDD- |
| | | LTE:Band1,Band3,Band5,Band7,Band8,Band20,Band2 |
| | | 8 |
| - | GPS | GPS+GLONASS+ Beidou, Supporting AGPS |
| | | GPS: L1+L5(1.575GHz); Beidou: B1(1.561GHz); |
| | | GLONASS: L1(1.602GHz) |
| | WPAN | |
| • | Bluetooth | Bluetooth 5.1 (supports BLE) |
| | Accessories | 565555 |
| 00 | Standard | Power Adapter(18W), USB Cable, Wrist Lanyard |
| 95 | Additional | Protective cover (including hand strap), Single device |
| | | charging cradle ,5-slot cradle, 4 batteries charger, |
| | | pistol grip |
| | Third Party Applic | cation Development Support |
| | System | Android 11 |
| | Software | |
| | System | Eclipse, Android Studio |
| | Programming | 20., poe, maiora ocadio |
| | Environment | |
| _ | | |







₃₉₄5565553





